yberoam[®]

Unified Threat Management

Gartner positions

Cyberoam UTM as a

"Visionary" in Magic

Quadrant for SMB

Multifunction

Firewalls :

Cyberoam CR100ia

Comprehensive Network Security for Small & Medium Offices











Cyberoam Unified Threat Management appliances offer assured security, connectivity and productivity to small and medium enterprises (SMEs) by allowing user identity-based policy controls.

Cyberoam's User Layer 8 Technology treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack. It attaches user identity to security, taking organizations a step ahead of conventional solutions that bind security to IP-addresses. This adds speed to an organization's security by offering instant visibility into the source of attacks by username rather than IP address - allowing immediate remediation to restore security or allowing proactive security. Layer 8 technology functions along with each of Cyberoam security features to allow creation of identity-based security policies.

Cyberoam's future-ready Extensible Security Architecture (ESA) offers an extensible platform that can grow with the future security needs of an organization without degrading system performance. ESA supports feature enhancements that can be developed rapidly and deployed with minimum efforts.

User Identity-based Security Policy Controls USER L8 **Application** L7 **F** 👙 🚮 L6 Presentation ASCII, EBCDIC, ICA Session **Transport** Network Data Link **Physical**

Cyberoam's Layer 8 Technology treats "User Identity" as the 8th Layer in the protocol stack

Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies

Cyberoam UTM features assure Security, Connectivity, Productivity



Security

Network Security

- Firewall
- Intrusion Prevention System - Wireless security

Content Security

- Anti-Virus/Anti-Spyware
- Anti-Spam
- HTTPS/SSL Content Security

Administrative Security

- Next-Gen UI
- iView- Logging & Reporting



Connectivity

Business Continuity

- Multiple Link Management
- High Availability

Network Availability

- 3G/WiMAX Connectivity

Future-ready Connectivity

- "IPv6 Ready" Gold Logo



Productivity

Employee Productivity

- Content Filtering
- Instant Messaging Archiving & Controls

IT Resource Optimization

- Bandwidth Management
- Traffic Discovery
- Application Layer 7 Management

Administrator Productivity

- Next-Gen UI

Specification

Interfaces	
Copper GbE Ports	6
Configurable Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45/DB9)	1
USB Ports	2
Hardware Bypass Segments	1*

System Performance**

System remornance	
Firewall throughput (UDP) (Mbps)	1250
Firewall throughput (TCP) (Mbps)	1000
New sessions/second	10,000
Concurrent sessions	400,000
168-bit 3DES/AES throughput (Mbps)	80/100
WAF Protected Throughput (Mbps)	60
Anti-Virus throughput (Mbps)	200
IPS throughput (Mbps)	300
UTM throughput (Mbps)	160

Stateful Inspection Firewall

- -Layer 8 (User Identity) Firewall -Multiple Security Zones -Access Control Criteria (ACC) User Identity, Source &
- Destination Zone, MAC and IP address, Service
 UTM policies IPS, Web Filtering, Application Filtering,
 Anti-Virus, Anti-Spam and Bandwidth Management
- Anti-Virus, Anti-Spam and Bandwidth Manag--Layer 7 (Application) Control & Visibility -Access Scheduling -Policy based Source & Destination NAT -H.323, SIP NAT Traversal -802.1q VLAN Support -DoS & DDoS Attack prevention -MAC & IP-MAC filtering and Spoof prevention

- Gateway Anti-Virus & Anti-Spyware
 Virus, Worm, Trojan Detection & Removal
 Spyware, Malware, Phishing protection
- -Automatic virus signature database update Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning Self Service Quarantine area Scan and deliver by file size

- Block by file types
- -Add disclaimer/signature

Gateway Anti-Spam

- Real-time Blacklist (RBL), MIME header check
 Filter based on message header, size, sender, recipient

- Filter based on message neader, size, sender, rec Subject line tagging IP address Black list/White list Redirect Spam mails to dedicated email address Image-based Spam filtering using RPD Technology Zero hour Virus Outbreak Protection
- Self Service Quarantine area Spam Notification through Digest
- IP Reputation-based Spam filtering

Intrusion Prevention System - Signatures: Default (3000+), Custom

- IPS Policies: Multiple, Custom User-based policy creation Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection DDoS attack prevention

- Web Filtering
 Inbuilt Web Category Database
 URL, keyword, File type block
 Categories: Default(82+), Custom
 Protocols supported: HTTP, HTTPS
 Block Malware, Phishing, Pharming URLs
 Schedule-based access control
 Custom block messages per gatagory

- Custom block messages per category
 Block Java Applets, Cookies, Active X
 CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

Application Filtering

- Inbuilt Application Category Database
- Application Categories: e.g. Gaming, IM, P2P, Proxy: 11+
- Schedule-based access control
- Block
 P2P applications e.g. Skype
 Anonymous proxies e.g. Ultra surf
 - "Phone home" activities
- Keylogger Layer 7 (Applications) & Layer 8 (User Identity) Visibility

- Web Application Firewall**

 Positive Protection model

 Unique "Intuitive Website Flow Detector" technology

 Protection against SQL Injections, Cross-site Scripting
 (XSS), Session Hijacking, URL Tampering, Cookie
 Poisoning

 Support for HTTP 0.9/1.0/1.1

 Extensive Logging & Reporting

 Back-end servers supported: 5

Virtual Private Network

- IPSec, L2TP, PPTP Encryption 3DES, DES, AES, Twofish, Blowfish,
- Serpent Hash Algorithms MD5, SHA-1
- Authentication Preshared key, Digital certificates
- IPSec NAT Traversal Dead peer detection and PFS support
- Diffie Hellman Groups 1,2,5,14,15,16
- External Certificate Authority support Export Road Warrior connection configuration Domain name support for tunnel end points
- VPN connection redundancy Overlapping Network support Hub & Spoke VPN support

SSL VPN

- -TCP & UDP Tunneling
- Authentication Active Directory, LDAP, RADIUS,
- Cyberoam Multi-layered Client Authentication Certificate, Username/Password

- User & Group policy enforcement
 Network access Split and Full tunneling
 Browser-based (Portal) Access Clientless access
 Lightweight SSL VPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls Session timeout, Dead Peer Detection, Portal customization
- TCP- based Application Access HTTP, HTTPS, RDP, TELNET, SSH

Instant Messaging (IM) Management - Yahoo and Windows Live Messenger - Virus Scanning for IM traffic

- Allow/Block Login Allow/Block File Transfer Allow/Block Webcam
- -Allow/Block one-to-one/group chat
- Content-based blocking IM activities Log
- -Archive files transferred
- Custom Alerts

Wireless WAN

- USB port 3G and Wimax Support* Primary WAN link WAN Backup link

- Bandwidth Management
 Application and User Identity based Bandwidth
- Management
- Guaranteed & Burstable bandwidth policy - Application & User Identity based Traffic Discovery
 - Multi WAN bandwidth reporting
 - Category-based bandwidth restriction

User Identity and Group Based Controls-Access time restriction

- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth Schedule based P2P and IM Controls

- Networking
 Failover Automated Failover/Failback, Multi-WAN failover, 3GModem failover
- WRR based load balancing
- Wrk based on Application and User Policy routing based on Application and User IP Address Assignment Static, PPPOE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay Support for HTTP Proxy Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast
- Forwarding
 Parent Proxy support with FQDN - "IPv6 Ready" Gold Logo

High Availability

- -Active-Active
- -Active-Passive with State Synchronization
- Stateful failover
- -Alerts on appliance status change

Administration & System Management

- Web-based configuration wizard
 Role-based access control
- Firmware Upgrades via Web UI Web 2.0 compliant UI (HTTPS) UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
 Multi-lingual support: Chinese, Hindi, French, Korean
 Cyberoam Central Console (Optional)
 NTP Support

User Authentication

- Internal database
 -Active Directory Integration
 -Automatic Windows Single Sign On
 -External LDAP/RADIUS database integration
 Thin Client support Microsoft Windows Server 2003
 Terminal Services and Citrix XenApp
- RSA securID support External Authentication Users and Administrators
- User/MAC Binding
 Multiple Authentication servers

- **Logging/Monitoring** Graphical real-time and historical monitoring
- Email notification of reports, viruses and attacks
- Syslog support Log Viewer IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

Cyberoam

On-Appliance Cyberoam-iView Reporting - Integrated Web-based Reporting tool -

- Cyberoam-iView
 1000+ drilldown reports
 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards Username, Host, Email ID specific Monitoring Dashboard
- Dasnoard
 Reports Security, Virus, Spam, Traffic, Policy
 violations, VPN, Search Engine keywords
 Multi-format reports tabular, graphical
 Exportable formats PDF, Excel
 Automated Report Scheduling

IPSec VPN Client***

- Inter-operability with major IPSec VPN Gateways
 Inter-operability with major IPSec VPN Gateways
 Supported platforms: Windows 2000, WinXP 32/64-bit,
 Windows 2003 32-bit, Windows 2008 32/64-bit,
 Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

- Certification
- ICSA Firewall Corporate Checkmark UTM Level 5 Certification VPNC Basic and AES interoperability
- "IPv6 Ready" Gold Logo

Compliance

CE FCC

Dimensions HxWxD (inches) 1.7 x 16.8 x 10.3 4.3 x 42.7 x 26.2 HxWxD(cms) Weight 5.3 kg, 11.68 lbs

Environmental Operating Temperature Storage Temperature

Relative Humidity (Non condensing)

Input Voltage Consumption Total Heat Dissipation (BTU) 100-240 VAC 90W 200

*If Enabled, will bypass traffic only in case of power failure. "Subscription available in all the Models of CR50ia & above. For further details refer to WAF Datasheet.

Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments. *Additional Purchase Required. *3G card and modem details are not included. See http://www.cyberoam.com for supported USB devices. **Subscription available in all the Models of CR50ia & above.



5 to 40 °C 0 to 70 °C

10 to 90%

Toll Free Numbers

USA: +1-800-686-2360 | India: 1-800-301-00013 APAC/MEA: +1-877-777-0368 | Europe: +44-808-120-3958 Copyright@1999-2013 Cyberoam Technologies Pvt.Ltd. AllRightsReserved. Cyberoam and Cyberoam logo are registered trademark of Cyberoam Technologies Pvt. Ltd. Although Cyberoam has templed to provide accurate information. Oyberoam assume no responsibility for accuracy or completeness of information neither is this a legally binding representation. Cyberoam has the right to Annaga, modity rander or otherwise revise the publication without notice. Pt-10-100222-100423